UL Online Certifications Directory

BNST.R8078 Fiber, Sprayed

Page Bottom

Fiber, Sprayed

See General Information for Fiber, Sprayed

NU-WOOL CO INC 2472 PORT SHELDON RD JENISON, MI 49428 USA R8078

Fiber for application with water to interior surfaces in accordance with directions for application supplied with product.

	Applied to Inorganic Reinforced Cement Board in a Max Thk of 5 In.+.
Flame spread	15
Smoke developed	5

⁺Must be applied with water in accordance with application instructions.

Last Updated on 2004-10-27

Questions? Notice of Disclaimer Page Top

Copyright © 2006 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2006 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

