

UL Online Certifications Directory

BPHX.R8078 Loose Fill Materials

[Page Bottom](#)

Loose Fill Materials

[See General Information for Loose Fill Materials](#)

NU-WOOL CO INC
2472 PORT SHELDON RD
JENISON, MI 49428 USA

R8078

Cellulosic fiber chemically treated to reduce its combustibility.

Classified in accordance with the following ASTM C739-97 Characteristics.

Flammability Characteristics	
Critical Radiant Flux	Greater than or equal to 0.12 w/cm sq
Smoldering Combustion	Less than or equal to 15.0 percent
Environmental Characteristics	
Corrosiveness	Acceptable
Fungi Resistance	Acceptable
Physical Characteristics	
Density (Settled)	1.6 pcf
Thermal Resistance	3.80 R/in (at 4 in. thickness)
Moisture Absorption	Acceptable
Odor Emission	Acceptable

[Last Updated](#) on 2006-02-20

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2006 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2006 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

